

**Customer**

SERCOM  
430 S. Link Lane, Fort Collins, CO 80524  
(970) 482-8410  
Jason Pacini  
pacinij@sercom-usa.com

**Calibration By**

SERCOM  
430 S. Link Lane, Fort Collins, CO 80524  
(970) 482-8410  
info@sercom-usa.com  
sercom-usa.com

**Date**

04/02/2021

**Next Calibration**

04/02/2022

**Balance** • Chemistry Department • Room 100

MANUFACTURER	MODEL	TYPE	MAX WEIGHT (g)	SERIAL	ASSET
Sartorius	SECURA225D-1S	Analytical	220	123456789	BAL-01

**Additional Action Taken**

Balance pan cleaned, balance leveled, balance housing cleaned.

**Remarks**

Unit in good condition. Minor issues with linearity observed.

**Results**

As found: PASS  
As left: PASS

**Service Technician**



Jason Pacini

**Room Conditions**

ROOM TEMP (°C)	HUMIDITY (%)
22.1	25

**NIST Traceability**

DEVICE	MANUFACTURER	SERIAL NO.	LAST CALIBRATION	NEXT CALIBRATION	TRACEABILITY NO.
Environmental Probe	Control Company	192413851	08/20/2019	08/20/2021	6530-10642150
Weight Set #2	Troemner	2	07/22/2020	01/31/2022	01144827-1

The calibration results published in this certificate were obtained using equipment capable of producing results that are traceable to and through NIST to the International System of Units. SERCOM is ISO/IEC 17025:2017 accredited by PJLA, accreditation number 60261. The reported expanded uncertainty of measurement is stated as the combined standard uncertainty of measurement multiplied by the coverage factor  $k = 2$  such that the coverage probability corresponds to approximately 95%. Decision rule is simple acceptance where the results are within specified tolerance without uncertainties.


## As Found

TEST WEIGHT (g)	INDICATION (g)	TOLERANCE (%)	ERROR (%)	RESULT
220	219.9986	0.1	0.0006	PASS

## Eccentricity

Eccentricity measures the error relating to variations in the positioning of weights on the weighing pan.

TEST WEIGHT (g)	INDICATION (g)	TOLERANCE ( $\pm$ g)	ECCENTRICITY (g)	RESULT
100		0.0003	0.0001	PASS



## Linearity

Linearity refers to the ability to deliver identical sensitivity throughout the weighing capacity of a balance.

TARE LOAD (g)	TEST WEIGHT (g)	INDICATION (g)	ERROR (g)	TOLERANCE ( $\pm$ g)	NON-TARED LINEARITY (g)	RESULT
1 N/A	0	0.0000	0.0000	0.0002	-0.0001	PASS
2 N/A	50	49.9999	-0.0001			
3 N/A	100	99.9999	-0.0001			
4 N/A	150	149.9999	-0.0001			
5 N/A	200	200.0000	0.0000			

TARE LOAD (g)	TEST WEIGHT (g)	INDICATION (g)	ERROR (g)	TOLERANCE ( $\pm$ g)	TARED LINEARITY (g)	RESULT
1 0	50	50.0000	0.0000	0.0002	-0.0001	PASS
2 50	100	49.9999	-0.0001			
3 100	150	49.9999	-0.0001			
4 150	200	50.0000	0.0000			

## Sensitivity

Sensitivity tests determine the minimum weight change that the balance can detect with a minimum readability of 0.0001.

TEST WEIGHT (g)	INDICATION (g)	TOLERANCE ( $\pm$ g)	SENSITIVITY (g)	RESULT
200	200.0000	0.0002	0.0001	PASS

## Repeatability

Repeatability refers to the ability to display the same value when a weight is placed on a scale more than one time.

TEST WEIGHT (g)	INDICATION (g)	ERROR (g)	TOLERANCE ( $\pm$ g)	REPEATABILITY (g)	RESULT	
100	1	100.0000	0.0000	0.0001	0.00004	PASS
	2	100.0000	0.0000			
	3	100.0000	0.0000			
	4	99.9999	-0.0001			
	5	100.0000	0.0000			
	6	100.0000	0.0000			
	7	100.0001	0.0001			
	8	100.0000	0.0000			
	9	100.0000	0.0000			
	10	100.0000	0.0000			

## As Left

TEST WEIGHT (g)	INDICATION (g)	TOLERANCE (%)	ERROR (%)	RESULT
220	220.0000	0.1	0.0000	PASS

## Expanded Uncertainty

The expanded uncertainty (U) combines uncertainties for readability, linearity, eccentricity, repeatability and sensitivity with  $k = 2$ .

U = 0.0002 g

The calibration results published in this certificate were obtained using equipment capable of producing results that are traceable to and through NIST to the International System of Units. SERCOM is ISO/IEC 17025:2017 accredited by PJLA, accreditation number 60261. The reported expanded uncertainty of measurement is stated as the combined standard uncertainty of measurement multiplied by the coverage factor  $k = 2$  such that the coverage probability corresponds to approximately 95%. Decision rule is simple acceptance where the results are within specified tolerance without uncertainties.